



since 1894 by

STOOPEN & meeûs

Technical Datasheet BadgeonAdditive

DESCRIPTION

BadgeonAdditive provides better adhesion on smooth, low-porous surfaces. Always be very careful in the case of painted surfaces. Removing the old paint layers is always the most safe and qualitative solution. Only well-adhesive and alkali-resistant paint layers may possibly be considered. This BadgeonAdditive is also able to improve adhesion on porous surfaces but it does not offer a solution on saturated surfaces, or surfaces treated with water-repellent products (e.g. siloxanes). Badgeon applied on old layers of paint creates an extra load for the old layer of paint due to the weight and the moisture retaining character of the Badgeon. It is the foreman's responsibility to assess the existing layers of paint. In case of doubts on the existing paint it must be removed. BadgeonAdditive can provide a solution if one does not want to remove the old paint, but adhesion will be better on a porous surface.

PACKAGING

Use 2 kg of BadgeonAdditive per 25 kg of Badgeon for the first layer on non-porous surfaces.

SUBSTRATE

Stable, non-porous substrates, such as painted brick or concrete must be clean and free from greases and corrosion. Existing layers of paint must be in good condition, any loose paint must be removed. Damaged paint in which little cracks, etc. are visible are more prone to let moisture through after badgeoning, which creates the risk of the underlying paint to come off sooner. Do not use Badgeon on non-alkali resistant paint and Lime Paint. If the substrate consists of porous and non-porous surfaces, the intake must be homogenised. It is preferred to remove the existing paint; alternatively a certain part of the porous surface can be treated with Stoopen & Meeûs StucPrimer.

PREPARATION

BadgeonAdditive is mixed with water along with the Badgeon.

TECHNICAL FEATURES

Type of delivery	White powder	as the poor absorption of the surface will reduce the intake.
pH	10 to 11	
Preparation water	Do not provide extra preparation water for the additive; do not make the Badgeon too flowable	In closed packaging, at least 1/2 years: dry
Cleaning	Water	

PRECAUTIONS

Mix Badgeon in open air or in well aerated space. Badgeon is a strong alkalic product. Carry protection gloves/protection clothing/eye protection/face protection. HAZARD: Causes severe eye injury. In case of CONTACT WITH THE EYES: Rinse off carefully for a couple of minutes. If possible, take off contact lenses. Keep on rinsing. Consult immediately a physician. WARNING: Causes skin irritation. IN CASE OF CONTACT WITH THE EYES: Wash with plentiful of water and soap. Can cause irritation of the airways. Avoid inhalation of dust. AFTER INHALATION: Take the person into the fresh air and take care that the person can breath easily. Keep out of reach of children.

NOTICE

Stoopen & Meeûs accepts the responsibility for the quality of its products, however does not accept any liability for the application of these products. Always consult the technical sheet of the product on the website.

E: info@stoopen-meeus.com
T: +32 (0)3 825 00 55

Rev. : 20 03 2019

Stoopen & Meeûs nv
Van Praetstraat 22 B-2660 Hoboken, Belgium
VAT: BE 0450 824 623

www.stoopen-meeus.com