



since 1894 by

STOOPEN & meeûs

Technical Datasheet UniWallPrimer

DESCRIPTION

Fast drying, universal, solvent-free synthetic resin dispersion primer for absorbent and non-absorbent substrates, suitable for finishing with alkaline products such as lime paint, clay paint... .

Impregnation for indoor and outdoor applications that decreases absorption and enhance adhesion.

APPLICATION

This primer can be used on stony materials, cement and gypsum plaster, aerated concrete, concrete, silicate stone, wood, MDF, etc. Not suitable for plastic or metal.

Use only on dry, stark and stable surfaces, free of dust, dirt, oils and greases or other separating layers.

SPECIFICATIONS

Density : $\pm 1.01 \text{ g/cm}^3$.

Solid content : approx. 20%.

Drying time: 1-12 hours, depending on conditions such as temperature, ventilation and substrate absorption.

Application temperature: 5°C - 25 °C.

STORAGE

Store in a cool, frost-free place for up to 2 years. Unopened in the original packaging.

COVERAGE

100-150 g/m² in 1 layer is usually sufficient. In case of strongly weathered substrates, a 2° wet-on-wet layer should be applied.

RECOMMENDED TOOLS

Brush, roller or airless equipment. Clean tools with water.

NOTICE

Stoopen & Meeûs accepts the responsibility for the quality of its products, however does not accept any liability for the application of these products.

Always consult the technical sheet of the product on the website.

Revision Date: 15 12 2017

E: info@stoopen-meeus.com
T: +32 (0)3 825 00 55

Stoopen & Meeûs nv
Van Praetstraat 22 B-2660 Hoboken, Belgium
VAT: BE 0450 824 623
www.stoopen-meeus.com