



since 1894 by

STOOPEN & meeûs

Technical Datasheet StucHardWaxOil

DESCRIPTION

StucHardWaxOil (SHWO) is a 'high solid', 1-component urethane modified alkyd oil with added wax. SHWO penetrates the Stuc and offers an almost invisible protection against the most common domestic stains and moisture. SHWO has a darkening and yellowing effect on the colour (specially in dark places) and has few sheens.

APPLICATION

Always stir and shake well before use, if necessary warm up or dilute with 5-10 % white spirit to improve the workability. Rub the SHWO in 2 very thin, uniform layers, until the complete SHWO has penetrated the Stuc. Dust dry after 1 hour. Waiting time between 2 layers, 10 hours. Attention: do not apply too much SHWO in edges or asperities, since this will result in yellow-brown discolorations. Do not apply more layers after these 2, only correct possible local damages.

UNDERGROUND

The Stuc must be completely dry. The rougher the finishing, the more difficult it will be to apply the SHWO.

SPECIFICATIONS

Based on natural vegetable oils and waxes. Contains oil drying agents. This product fulfils the EU regulation 2004/42/EG, max. VOC content < 500 g/L (Cat. i – SG 2010)

STORAGE

Store without opening in a cool environment, for 5 years.

CONSUMPTION

Apr. 0,5 litre / 10 m² in 2 layers, depending on the absorption power of the Stuc.

RECOMMENDED TOOLS

Lint-free synthetic sponge. Brush, knife or roll are NOT appropriate. Clean the material with white spirit. Store the sponges that have been soaked in liquid product immediately in a hermetically closed container (hazard of spontaneous combustion).

MAINTENANCE

Do not charge during the first 24 hours. If after a certain time there are dark stains due to moisture, correct the SHWO locally. In case of much dirt, try to eliminate the SHWO with acetone or by polishing lightly, and then apply again.

PRECAUTIONS

Flammable liquid and vapour. Can cause drowsiness or dizziness. Repeated exposure can cause a dry or cracked skin. Avoid inhalation of mist/vapour. Only use outside or in a good aerated space. Carry protection gloves/protection clothing/eye protection/face protection. In case of CONTACT WITH THE SKIN (or with the hair): take off the soiled clothes immediately. Rinse skin with water or shower. AFTER INHALATION: Take the victim into the fresh air and let the victim rest in a position facilitating the breathing. Contains: hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclical, < 2% aromates.2. Contains: 2-butanone oxime, cobalt soap. Can cause an allergic reaction.

E: info@stoopen-meeus.com
T: +32 (0)3 825 00 55

Rev. : 24/05/2019

Stoopen & Meeûs nv
Van Praetstraat 22 B-2660 Hoboken, Belgium
VAT: BE 0450 824 623

www.stoopen-meeus.com



since 1894 by

STOOPEN & meeûs

NOTICE

Stoopen & Meeûs accepts the responsibility for the quality of its products, however does not accept any liability for the application of these products. Always consult the technical sheet of the product on the website.

E: info@stoopen-meeus.com
T: +32 (0)3 825 00 55

Rev. : 24/05/2019

Stoopen & Meeûs nv
Van Praetstraat 22 B-2660 Hoboken, Belgium
VAT: BE 0450 824 623

www.stoopen-meeus.com