



since 1894 by

STOOPEN & meeûs

Technical Datasheet StucVernisPUHardener

FEATURES

Hardener for transparent, 2 component polyurethane varnish based on water, for inside application.

APPLICATION

Mix and stir the Hardener with PU, with the ratio 1:3, afterwards starting from the second layer, if necessary, add 5% water and let rest for 10 minutes.

STORAGE

Store in a cool and frost-free environment for 6 months.

SAFETY

Hazards:

Inflammable liquid and vapour. Can cause an allergic skin reaction. Causes severe eye irritation. Can cause irritation of the airways. Harmful for the organisms living in water, with long term consequences.

Keep out of reach of heat/sparks/open fire/hot surfaces. Do not smoke. Avoid the inhalation of mist/vapour.

Only use outside or in a well aerated space. Wear protection gloves / clothes / eye protection / face protection.

IN CASE OF CONTACT WITH THE SKIN (or the hair): take off immediately the soiled clothes – rinse / shower the skin with water. AFTER INHALATION: Take the victim into the fresh air and let the victim rest in a position facilitating the breathing. When the victim gets unwell, consult a poison control centre or a physician.

Additional risk features and labelling elements:

Contains isocyanates. Can cause an allergic reaction. EU regulation 2004/42/EG, max. VOC content 60 g/L (Cat. A/j – SG 2010).

NOTICE

Stoopen & Meeûs accepts the responsibility for the quality of its products, however does not accept any liability for the application of these products. Always consult the technical sheet of the product on the website.

E: info@stoopen-meeus.com
T: +32 (0)3 825 00 55

Rev. : 21/02/2019

Stoopen & Meeûs nv
Van Praetstraat 22 B-2660 Hoboken, Belgium
VAT: BE 0450 824 623

www.stoopen-meeus.com