



since 1894 by

STOOPEN & meeûs

Technical Datasheet StucVernisSolventPU

DESCRIPTION

Transparent, fast drying, solvent supported 2K polyurethane varnish for interior. StucVernisSolventPU (SVSPU) provides Stuc with a good chemical and physical resistance. Protects the Stuc from most household stains, with sufficient layer thickness.

APPLICATION

Apply SVSPU in at least 2 layers, the first layer needs to be reasonably saturated to prevent starting (depending on the structure and load; apply extra layers if necessary). Mechanically mix the hardener with PU in a ratio of 1:10. Pot-life: 8 hours at 20°C.

Smoothly spread the SVSPU with the roll in multiple subsequent layers in various directions, with an intermediate drying time of at least 60 minutes. Dust dry after 20 minutes. Avoid overlaps on dark colours and large surfaces. Check afterwards if the SVSPU is completely closed. Full hardening after 7 days; avoid contact with water before.

UNDERGROUND

The underground must be clean and completely dry.
Cond: 15 to 25°C and with a relative humidity of the environment of 40-70%.

SPECIFICATIONS

SVSPU slightly darkens the colour of the Stuc, depending on the colour.

STORAGE

Can be kept in a well-ventilated, cool and frost protected place for 1 year.

CONSUMPTION

Approx. 1 litre / 5 m²

RECOMMENED TOOLS

Foam lacquer roller.

SAFETY

Hazard statements:

Highly flammable liquid and vapour. Harmful when in contact with the skin. Harmful when inhaled. Causes skin irritation. Causes severe eye irritation. May cause respiratory irritation. May cause sleepiness or dizziness. Repeated exposure may cause a dry or cracked skin. Can cause damage to organs in the event of prolonged or repeated exposure. Can be lethal if the substance comes in the airways when ingested.

Precautions:

Keep away from heat/sparks/open fire/hot surfaces. Do not smoke. Avoid inhalation of vapour, spray mist. Take precautionary measures against any discharge of static electricity. Wear protective gloves, eye protection. IF INGESTED: immediately consult a POISON CONTROL CENTRE or a doctor. WHEN IN CONTACT WITH THE SKIN (or hair): Immediately remove any contaminated clothing. Wash the skin with water/take a shower. In the event of skin irritation: consult a doctor. IF INHALED: take the victim in the open air and let them rest in a position that allows easy breathing. In the event one feels unwell, always consult a POISON CONTROL CENTRE or a doctor.

Contains: n-Butylacetate, Xylene (mixture), 4-Metyl-2-pentanone. EU Regulation 2004/42/EG, max. VOC content of 499 g/L (Cat. A/h – SG 2010).

NOTICE

Stoopen & Meeûs accepts the responsibility for the quality of its products, however does not accept any liability for the application of these products. Always consult the technical sheet of the product on the website.

E: info@stoopen-meeus.com
T: +32 (0)3 825 00 55

Stoopen & Meeûs nv
Van Praetstraat 22 B-2660 Hoboken, Belgium
VAT: BE 0450 824 623

Rev. : 28/08/2018

www.stoopen-meeus.com