



Anc. Ets.

STOOPEN & meeûs

SINCE  
1894

## TECHNICAL DATASHEET : StucSoap

### DESCRIPTION:

StucSoap is a natural soap for protecting, cleaning and maintenance of STUC Deco and STUC Granito. The oily natural soap lays a protective film against dirt.

### PACKAGING:

StucSoap comes in packs of 5 kg and 2kg.

### TECHNICAL SPECIFICATIONS:

|                   |  |
|-------------------|--|
| Delivery form:    | light yellow liquid – ready to use   |
| pH:               | 9-10   |
| Odor:             | mild   |
| Number of layers: | 1 or 2 layers  |
| Consumption:      | about 1 liter / 20 m <sup>2</sup> , depending on the porosity of the surface   |
| Drying time:      | about 2 hours between 2 layers (depending on climatic conditions)              |
| Temperature:      | surface temperature > +5 ° C processing temperature between +5 ° C and +25 ° C |
| Shelf Life:       | store in a cool, frost-free environment, for at least 5 years.                 |
| Tools:            | lint-free, synthetic sponge  |
| Tool cleaning:    | water  |

### SURFACE:

STUC Deco and STUC Granito. The surface should be completely dry.

### INSTRUCTIONS:

Recommended tools: lint-free, synthetic sponge  
Apply StucSoap in 1 to 2 undiluted coats with a sponge, without leaving too much foam behind.  
Remove excess StucSoap or dried foam with a damp sponge.  
Cleaning and maintenance: StucSoap 0.5 liters in 10 liters of warm water solution.  
Maintenance frequency depends on pollution and stress.  
Reapply if STUC absorbs moisture.

### PRECAUTIONS:

Keep from freezing.  
DIN 53-160, EN 71-3, no harmful ingredients.

### NOTE:

Stoopen & Meeûs guarantees the highest quality of its products, however it does not accept any liability for the improper application of its products.

Anc. Ets. Stoopen & Meeûs  
Van Praetstraat, 22  
B-2660 Hoboken  
Tel. 32 3 825 00 55

Site : [www.stoopen-meeus.com](http://www.stoopen-meeus.com)  
Email : [dragon@stoopen-meeus.com](mailto:dragon@stoopen-meeus.com)  
Revisedatum : 03/12/2014